PROFLEX



TRX1 Elite Electric Treadmill

User Manual

[Revision 1.0 August 2017]

READ THIS MANUAL CAREFULLY BEFORE USE – FAILURE TO DO SO MAY RESULT IN INJURY, PROPERTY DAMAGE AND MAY VOID WARRANTY. • KEEP THIS MANUAL FOR FUTURE REFERENCE. • Products covered by this manual may vary in appearance, assembly, inclusions, specifications, description and packaging.

E&OE © 2017 Proflex



Safety

Basic precautions, including the following important safety instructions, should always be followed when using this equipment. Read all instructions before use.



To reduce the risk of electric shock, always unplug the equipment from the electrical outlet after use and before cleaning, assembling, or servicing. Failure to follow these instructions may lead to personal injury and cause damage to the equipment.

Before beginning any exercise program, consult your physician. This is especially important for people over 35 years of age or who have pre-existing health problems. Read all instructions before using any fitness equipment. Do not operate this exercise equipment without properly fitted guards, as the moving parts can present a risk of serious injury if exposed.

- Use this product for its intended use only as described in this user manual. Do not use attachments not supplied or recommended by the manufacturer.
- Never operate the unit with a damaged cord or plug, or if it is malfunctioning. If it has been dropped, damaged or exposed to water, have the unit inspected/repaired by an authorized service center.
- If the supply cord is damaged, it must be replaced by the manufacturer, its service agent or similarly qualified persons in order to avoid it being a potential hazard.
- This equipment must be plugged into a nominal 240VAC / 50Hz outlet that is properly grounded.
- Caution To avoid injury, use caution when stepping on to or off the equipment.
- Maximum weight capacity = 100 kg.
- Do not attempt any maintenance or adjustments other than those described in this user manual. Should any problems arise, discontinue use and consult an authorized service centre or personnel.
- Any information or data provided by the equipment is a guide only and is not to be used as medical data or scientific evidence.
- Never operate the equipment with the air openings blocked. Keep the air openings free of lint, hair, and other obstructions.
- Do not use the unit outdoors.
- Do not pull the equipment by its power cord or use the cord as a handle.
- Keep children and pets away from the equipment while in use.
- Elderly or disabled users should only use the equipment in the presence of an adult who can provide assistance if required.
- Do not operate where aerosol (spray) products are in use or where adequate oxygen is not available.
- Keep dry do not operate in wet or moist conditions.
- The motor cover can become hot while the equipment is in use. Do not place the equipment on flammable surfaces.
- Keep the electrical cord away from hot surfaces.
- Keep the equipment on a solid, level surface with a minimum safety area clearance of two meters around it. Be sure the area around the equipment remains clear of any obstructions during use.
- This equipment is for domestic household use only.
- One person only should use the equipment at a time.
- Wear comfortable and suitable clothing when using the equipment. Do not use the equipment barefoot or in socks. Always wear appropriate, enclosed athletic footwear. Never wear loose or baggy clothing as it can become caught on the equipment and create a hazard.
- Always hold on to the handrails while using the equipment.
- Always ensure the belt platform is securely in place when folding and moving the equipment.
- Do not leave children unsupervised near or on the equipment.
- Children should not be allowed to play or operate the equipment at any time.
- To disconnect, turn all controls to the OFF position, then remove plug from the wall outlet.



- This equipment is not intended for use by persons (including children) with reduced physical, sensory or mental capabilities, or lack of experience and knowledge, unless they have been given supervision or instruction concerning use of the equipment by a person responsible for their safety.
- Remove the safety tether for emergency stop.
- Keep hands clear of all moving parts. Never place hands or feet under the equipment while in use.
- Do not use the equipment on high-pile carpet greater than 1.3 cm in height.
- Before using the equipment, check that the belt is aligned and centred on the running deck and all visible fasteners on the equipment are sufficiently tightened and secure.
- Never operate this equipment when folded.
- Allow the running belt to fully stop and unplug the power cord from the wall outlet before folding the
 equipment.
- Always face towards the console and do not run backwards on the running belt.



Table of Contents

Safety	2
Parts Identification	5
Assembly	6
Operation	8
Safety Tether and Emergency Stop	8
Program and Manual Modes	8
Console and Functions	8
Manual Mode Training	10
Setting a Pre-Set Session Duration	10
Setting a Pre-Set Session Distance	10
Setting a Target Calorie Value	10
Program Mode Training	11
Care, Maintenance and Troubleshooting	12
Cleaning	12
Storage	12
Troubleshooting	12
Maintenance	13
Belt Lubrication	13
Belt Alignment and Tension Adjustment	13
Specifications	13
Warm-Up and Cool-Down Routine	14



LET PROFIET TRX1 Elite Electric Treadmill

PROFLEX

Parts Identification

The equipment comes most assembled, with the following parts. Ensure that all parts are included before assembly.



No.	Qty.	Description	No.	Qty.	Description
1	0(1)	Treadmill (includes belt platform, console, motor, handlebar etc)	4	1	Fasteners / Tools: M8x30 Screw (2)
2	1	Safety Tether		+	M8 Washer (2) M8 Lock Bolt
3	1	Belt Lubricant	,		Spanner / Screwdri 5mm and 6mm Alle
. 9	<i>(</i> -	Profile	8 P	Q	R PK
LEX		t clet let cl		EX	ELET
LEY	30k	PROFILET PROFILET PROFIL	PROF		PROFILET PROFI
at v		PROFIET PROFIET	+ PRO	Et	at .
Et	20KV	OFIL POFIL	20		offly agoff
1		PROFILET PRO	+ 6,	4	POFLET PROFI
	FILE	CELL SEIEL OFF	, K	Kr	OFILE OF
LEX P	, C.	BE BEO. BE	PRO.		PROFILET PROFI
et		t et let e	F .	CLEX	LET C
ET	ROFIL	PROFIET PROFIET PROFILE	PRO		Soft, bbo,
Et		© 201	+	Et	PROFILET PROFIL
E&OE	OFLE	© 201	7 Proflex		OFIL OFIL
PR	20	br bbs bk	PR	4	by bbs
1				45	

ption	PROFIET	No. Qty.	Description	ROFFE	ROFLE, PR
nill (includes belt platfo e, motor, handlebar et	orm,	45 1	Fasteners / Tools: M8x30 Screw (2) M8 Washer (2) M8 Lock Bolt Spanner / Screwdriver	POR (4)	PLEY OF
Tether bricant Properties Propert	PROFILET	20FLET	Pescription Fasteners / Tools: M8x30 Screw (2) M8 Washer (2) M8 Lock Bolt Spanner / Screwdriver 5mm and 6mm Allen Key	POFIET S	OF LET PR
FLET PROFILET	PROFIET	ROFLET	ROFLET PROFILET	POFIET	ROFLET
SFIE PROFILEY	PROFILE	OFLET.	PROFILE PROFILET	PROFILE,	OFILEX
FLET PROFILE	PROFIET	ROFLE	ROFIET PROFILE	POFIET	POFILE.
SFIE, PROFILE	© 2017 Pro	flex	PROFILE, PROFILET	PROFILE.	5 LET P



Assembly

Take all parts out of the carton and place them on a firm, flat surface. Remove all packing materials.

Et PROFIET

FLEX PROFILEY

PROFILET

With the equipment base (1) flat, lift the handle assembly (2) so that it is upright, then insert the M8 locking bolt (3) through the handlebar on the left-hand side of the machine and into the belt platform bracket (A). Firmly tighten the bolt by hand.



the handle columns, then secure it using 2 M8 screws (5) and washers (6). Tighten the screws (rotate right) using the Allen key.





Folding / Unfolding



Always set-up the equipment on a flat and level surface. If the equipment "rocks", (if applicable) rotate the feet under the front of the machine to move up or down as needed so the equipment is

To fold, remove (rotate left) the locking bolt (**A**) securing the belt platform (**B**) to the handlebar assembly (**C**). Lift the end of the belt platform (**B**) until it is vertical, then secure it to the handlebar assembly at location **X** using the locking bolt (**A**). Firmly tighten the bolt by hand.

To unfold, hold the belt platform firmly, then remove (rotate left) the locking bolt from location **X**. Gently lower the belt platform down so it rests on the floor. Secure the belt platform to the handle assembly using the locking bolt (**A**) and firmly tighten by hand (rotate right), against the handle mounting frame



Moving

The unit can be tilted onto its wheels for easy moving and storage.

With the equipment in the folded and locked position, firmly grasp the handlebar with both hands. Next, carefully tilt the equipment back until it rolls freely on the transport wheels.





Do not attempt to move the equipment while it is in the unfolded position.





Operation

Safety Tether and Emergency Stop

The equipment comes equipped with a "safety tether" (**C**). The safety tether must be attached to the console in order for the equipment to run. It is designed to attach to your clothing so that if you leave or fall from the equipment it will stop automatically, helping prevent injury.

Before beginning a workout session, ensure that the safety tether is properly placed onto the console and that the clip is securely attached to your clothing.



Note: If the equipment is on, but the safety tether is not attached, "- -" shows on the display and the equipment cannot be started.

Program and Manual Modes

The equipment features two basic operating modes:

Note: The equipment must not be running in order to change or select modes.

Manual Mode – The equipment is being used, but not running a pre-set program (see Program mode, below). In this mode, the equipment can be set to stop automatically at a pre-set session duration, distance or calories used value. To enter Manual mode, press MODE (see Manual Mode Training).

Note: You can also press **START** to use the equipment without setting a duration or distance. In this mode, the equipment will stop automatically after 60 minutes.


Program Mode – The equipment runs through a pre-set routine where it will apply a particular speed for a period of time. There are 12 pre-set routines to choose from ("P1" to "P12"). In Program mode, the unit automatically changes speeds. At each speed change, the unit beeps for 3 seconds before changing speed, as a warning. To enter Program mode, press PROG when the equipment is on but not running – the display flashes "P01". Press PROG until you reach the required program (see Program Mode Training).

Console and Functions

The equipment features a computerized display that provides you with controls for operating the unit as well as workout information, such as duration, speed, distance travelled etc.

To use the equipment:


- 1. Plug the equipment into the electrical supply.
- Place the power switch (D), located at the front of the unit, in the "ON" ("I") position.
- Attach the safety tether to the safety tether location on the console.
- Operate the equipment as desired.





Always stand on the side rails when starting the equipment. Never stand on the belt then start the machine.

















SPEED

MODE

mounted + and - buttons.

program time value.

distance or calories target values.

START

STOP

PROG

SPEED

Control Description Shows current information, such as current speed, elapsed or remaining time, used or Display remaining calories, current pulse etc. The range of values for each is: Time - 5:00 to 99:59 minutes / seconds. **Distance** – 1.0 to 99.9 kilometres. **Speed** -0.8 to 14.0 km/h. Calories - 20.0 to 999 calories. Pulse - 50 to 200 beats/minute (BPM). Shows above "♥" symbol. Note: When displaying pulse, you must have both hands on the metal sensors on each handle. • To approximately convert calories to kilojoules, multiply the number of calories by 4. **START** Press to start the equipment. STOP Press to stop the equipment. **PROG** Press to select a pre-set program. Each press moves to the next program in sequence (P1 to P2, P2 to P3 and so on). Hold the button down to more quickly step through programs. MODE When in Manual mode and the equipment is not running, press to switch between time, distance or calorie setting options. SPEED When the equipment is running, press + to increase speed. Press - to reduce speed. Each press changes speed by 0.1 km/h. Hold the button down to more quickly change speed. The speed range is 0.8 to 14.0 km/h. Speed can also be adjusted using the right-hand handle

When in Manual mode and the equipment is not running, press + or - to adjust either time.

When in Program mode and the equipment is not running, press + or - to adjust the



Manual Mode Training

"Manual" mode operation gives you the freedom to adjust the equipment operation as desired at any time. In this mode, once started, the equipment runs until you stop it or can be pre-set for a session duration, distance or target number of calories to use.

- Turn on the equipment.
- 2. Press START. The equipment counts down 3 seconds, then starts running at the slowest speed.
- 3. Adjust speed using + and as required.
- 4. When finished, press STOP.

Setting a Pre-Set Session Duration

When training to a pre-set session duration, the equipment stops automatically once the timer counts down to 0.00

- Turn on the equipment.
- Press MODE so that "TIME" is flashing at the bottom of the display.
- 3. Adjust the session duration using + and as required. Duration can range from 5 to 99 minutes.
- Press START. The equipment counts down 3 seconds, then starts running at the slowest speed.
- 5. Adjust speed as required.

Setting a Pre-Set Session Distance

When training to a pre-set session distance, the equipment stops automatically once the travelled distance reaches 0.00.

- 1. Turn on the equipment.
- Press MODE so that "DIS" is flashing at the bottom of the display.
- Adjust the session distance using + and as required. Distance can range from 1 to 99 km, in 1.0 km increments.
- Press START. The equipment counts down 3 seconds, then starts running at the slowest speed.
- Adjust speed as required.

Setting a Target Calorie Value

When training to a target calorie value, the equipment stops automatically once the number of calories used for the session reaches the target value.

- Turn on the equipment.
- 2. Press MODE so that the "CAL" is flashing at the bottom of the display.
- Adjust the target calorie value using + and as required. The value can range from 10 to 990 calories, in 1 calorie increments.
- 4. Press **START**. The equipment counts down 3 seconds, then starts running at the slowest speed.
- Adjust speed as required.



LET PROFILET PROFILEY

Et PROFIET FLEX PROFILET The equipment has 12 automatic training programs, "P1" to "P12". Each program has a standard duration of 30 minutes (you can change this) and applies differing speeds and gradients 20 times per program (for example, if the duration is 40 minutes, the speed changes every 2 minutes). To access the pressing PROG as required

PROFILET

- PROFILET PRO
- To change program duration, use and as required to set duration between 8 and 99 minutes.
- Press **START**. The equipment counts down 3 seconds, then the belt starts running.
- When the equipment changes speed, a beep sounds several times before the change.
- When completing the program, a beep sounds several times before the equipment stops.

P1	Program s		20 GI	20		20		S	O _K	S	peed	(km/h)	ROY		20		Ó	RO		0
P2 2 4 4 5 6 4 6 6 6 4 5 6 4 4 4 2 2 5 4 P3 2 4 4 6 6 4 7 7 7 4 7 7 4 4 4 2 4 5 3 P4 2 5 5 6 7 7 5 7 7 8 8 5 9 5 5 6 6 4 4 P5 2 4 4 5 6 7 7 5 6 7 8 8 5 4 3 3 6 5 4 4 2 5 4 3 P6 2 4 3 4 5 3 4 5 3 3 6 6 5 3 P8 2 3 3 3 4 5 3 4 5 6 7 4	- 0	2	13	3	4	5	3	4	5	5	5	3	4	5	4	4	4	2	3	5
P4 2 5 5 6 7 7 5 7 7 8 8 5 9 5 5 6 6 4 4 P5 2 4 4 5 6 7 7 5 6 7 8 8 5 4 3 3 6 5 4 P6 2 4 3 4 5 4 8 7 5 7 8 3 6 4 4 2 5 4 3 P7 2 3 3 3 4 5 3 4 5 3 3 3 6 6 5 3 P8 2 3 3 6 7 7 4 6 7 4 4 4 4 4 2 3 4 4 8 9 9 4 4 4 4 <td>P2</td> <td>2</td> <td>4</td> <td>4</td> <td>5</td> <td>6</td> <td>4</td> <td>6</td> <td>6</td> <td></td> <td>4</td> <td>5</td> <td>6</td> <td>4</td> <td>4</td> <td>4</td> <td>2</td> <td>2</td> <td>-</td> <td>4</td>	P2	2	4	4	5	6	4	6	6		4	5	6	4	4	4	2	2	-	4
P5 2 4 4 5 6 7 7 5 6 7 8 8 5 4 3 3 6 5 4 P6 2 4 3 4 5 4 8 7 5 7 8 3 6 4 4 2 5 4 3 P7 2 3 3 3 4 5 3 4 5 3 4 5 3 4 5 3 4 5 3 4 5 3 4 4 4 2 5 4 4 P8 2 3 3 6 7 7 4 6 7 4 4 4 4 2 3 4 4 P9 2 4 5 6 7 5 4 6 8 8 6 6 5 4 <td>P3</td> <td>2</td> <td>4</td> <td>4</td> <td>6</td> <td>6.0</td> <td>4</td> <td>7</td> <td>7</td> <td>7</td> <td>4</td> <td>7</td> <td>7</td> <td>4</td> <td>4</td> <td>4</td> <td>2</td> <td>4</td> <td>5</td> <td>3</td>	P3	2	4	4	6	6.0	4	7	7	7	4	7	7	4	4	4	2	4	5	3
P6 2 4 3 4 5 4 8 7 5 7 8 3 6 4 4 2 5 4 3 P7 2 3 3 3 4 5 3 4 5 3 4 5 3 4 4 2 5 4 3 P8 2 3 3 6 7 7 4 6 7 4 4 4 2 3 4 4 P9 2 4 4 7 7 4 7 8 4 8 9 9 4 4 4 5 6 3 3 P10 2 4 5 6 7 5 4 6 8 8 6 6 5 4 4 2 4 4 3 P11 2 4 5 9	P4	2	5	5	6	7	7	5	7	78	8	8	5	9	5	5	6	6	4	4
P7 2 3 3 4 5 3 4 5 3 4 5 3 4 5 3 3 3 6 6 5 3 P8 2 3 3 6 7 7 4 6 7 4 4 4 2 3 4 4 P9 2 4 4 7 7 4 7 8 4 8 9 9 4 4 4 5 6 3 3 P10 2 4 5 6 7 5 4 6 8 8 6 6 5 4 4 2 4 4 3 P11 2 4 5 9 5 5 5 5 5 5 9 9 5 5 4 P12 2 5 8 10 7 <td< td=""><td>P5</td><td>2</td><td>4</td><td>4</td><td>5</td><td>6</td><td>7</td><td>7</td><td>5</td><td>6</td><td>7</td><td>- 8</td><td>8</td><td>5</td><td>4</td><td>3</td><td>3</td><td>6</td><td>5</td><td>4</td></td<>	P5	2	4	4	5	6	7	7	5	6	7	- 8	8	5	4	3	3	6	5	4
P8 2 3 3 6 7 7 4 6 7 4 4 4 2 3 4 4 P9 2 4 4 7 7 4 7 8 4 8 9 9 4 4 4 5 6 3 3 P10 2 4 5 6 7 5 4 6 8 8 6 6 5 4 4 2 4 4 3 P11 2 4 5 9 5 5 5 9 5 5 5 9 9 8 7 6 P12 2 5 8 10 7 7 10 10 7 7 10 10 6 6 9 9 5 5 4	P6	2	4	3	4	5	4	8	7	5	7	8	3	6	4	4	2	5	4	3
P9 2 4 4 7 7 4 7 8 4 8 9 9 4 4 4 5 6 3 3 P10 2 4 5 6 7 5 4 6 8 8 6 6 5 4 4 2 4 4 3 P11 2 4 5 9 5 5 5 9 5 5 5 9 9 8 7 6 P12 2 5 8 10 7 7 10 10 6 6 9 9 5 5 4	P7	2	3	3	3	4	5	3	9 4	5	3	4	5	3	3	3	6	6	5	3
P10 2 4 5 6 7 5 4 6 8 8 6 6 5 4 4 2 4 4 3 P11 2 4 5 9 5 9 5 5 5 9 9 8 7 6 P12 2 5 8 10 7 7 10 10 6 6 9 9 5 5 4	P8	2	3	3	6 <	7	7	4	6	7	4	6	7	4	4	4	2	3	4	4
P11 2 4 5 9 5 9 5 5 9 5 5 9 9 8 7 6 P12 2 5 8 10 7 7 10 10 6 6 9 9 5 5 4		_ ~		\vdash		_	\sim			-	-				1				427	-
P12 2 5 8 10 7 7 10 10 7 7 10 10 6 6 9 9 5 5 4			-		1				K -		-0		- 30			D				_
ET PROFILET	0>				<u> </u>	40.				-0					Q .					~ ~
t PROFIET PROF	P12	2	5	8	10	* 7	7	10	10	7	7	10	10	6	6	9	9	5	5	4
	EX	E	- 0	ROE	EX	ROK!	ET	PR	OFLE	P	OFI	et «	2ROF	E				ROFF	Et	PR



Care, Maintenance and Troubleshooting

Some maintenance activities described may be beyond the scope of some users. For procedures that you are not comfortable with or have the tools, knowledge or experience for have the unit serviced by a service centre or qualified technician. • To prevent electrical shock, switch OFF and disconnect the equipment from the electrical supply before cleaning or performing any maintenance tasks. • Before each use, check the running belt for wear.

Cleaning

The equipment can be cleaned with a soft cloth and mild detergent. Do not use abrasives, solvents or harsh chemicals. Be careful not to get excessive moisture on the display panel as this may damage it and create an electrical hazard.

After each use, wipe the unit of any sweat, dirt or liquids. Pay extra attention to the edges of the belt, where it meets the running boards on each side of the running belt– keeping this area clean will help prolong the life of the unit and maintain its performance. Keep the equipment, especially the display console, out of direct sunlight to prevent damage to the screen.

Storage

Store the equipment in a clean and dry indoor environment. Never leave or use the unit outdoors. Ensure the master power switch is OFF ("O") and the power cord is un-plugged from the mains electrical supply.

Troubleshooting

The following information may assist in identifying a problem and rectifying it.

Problem	Potential Reason	Correction
Equipment will not start.	A. Equipment not plugged in. B. Safety tether not in place.	A. Connect unit to mains electrical supply. B. Place safety tether in correct location.
Belt slips.	Belt loose.	Adjust belt tension.
Belt hesitates when stepped on.	A. Not enough lubrication on running deck. B. Belt too tight.	A. Lubricate running deck. B. Adjust belt tension.
Belt is not centred.	Running belt tension not even across the rear roller.	Adjust belt alignment.
Display shows "E01" or "- -"	Safety tether not in place.	Place safety tether in correct location on console.
Display shows "E02"	Low voltage detected / fuse failure.	Check mains electrical supply is to specifications. • Check drive unit and motor connections - if the motor is damaged, replace it.
Display shows "E03" or "E04"	Electrical protection tripped.	Check mains electrical supply is to specifications. • Ensure that drive belt is not caught or is unable to rotate due to obstruction. • Check all connections. • Check for motor or control circuitry fault (often indicated by a burning smell) and replace parts as required.
Display shows "E05"	Speed sensor problem detected.	Check all connections - if the sensor or control unit is damaged, replace it.
Equipment unsteady	Surface not flat.	Set-up equipment on a flat surface. • If applicable, rotate feet under front of machine to move up or down as needed so equipment is steady.

When to Call for Help

This equipment is designed with user safety as a priority. In the event of electrical failure, the equipment will shut off automatically to prevent injury and damage to the unit. If you encounter unusual behaviour from the equipment, turn the power switch off and on to reset the equipment. This should ready the equipment for



normal operation again. If after you have reset the equipment that it is still not operational, call an authorized service centre or technician for servicing.

Maintenance

Belt Lubrication

Lubricating the running belt helps maintain performance and extends service life. Lubricate the belt after the first 25 hours of use (or 2 to 3 months), then every 50 hours of use (or 5 to 8 months, or more frequently under extended usage).

To check if the belt requires lubrication, lift each side of it and feel the top surface of the running deck. If the deck is slick to the touch, no lubrication is required; if it is dry, lubricate.

To apply lubricant

- 1. Start the machine and run it at the highest speed setting.
- Place several drops of the supplied lubricant through the lubrication hole (E).
- Run on the equipment at a slow speed for 3 to 5 minutes to evenly distribute lubricant.






Do not over lubricate. Wipe away any excess lubricant from the running belt. • All-purpose household oil or sewing machine oil can also be used.

Belt Alignment and Tension Adjustment

The running belt is pre-adjusted to the running deck at the factory, but after prolonged use it can stretch and require re-tensioning. To adjust the belt, turn on the main power switch of the equipment and let the belt run at a speed of 6km/h. Use the Allen key provided to turn the rear roller adjustment bolts in order to centre the belt. If the running belt is shifting to the left, turn the left adjustment bolt 1/4 turn to the right, and the running belt should start to correct itself.

If the running belt is shifting to the right, then turn the right adjustment bolt 1/4 turn to the left, and the belt should start to correct itself. Keep turning the adjustment bolts until the running belt is properly centred.



If the running belt is slipping during use, turn off and unplug the equipment. Using the Allen key provided, turn both left and right rear roller adjustment bolts 1/4 turn to the right, then turn the main power switch back on and run the equipment at a speed of 6km/h. Run on to the running belt to determine if the belt is still slipping. Repeat this procedure until the belt no longer slips.

Specifications

Electrical	24	10VAC / 50Hz	OKY	00,	OFF	50,	20%
Weight Capacity	10	00kg	PK.	8,	8K	2.	8/4
Speed	0.	8 to 14.0km/h		4		4	
Belt Platform Size	10	050 x 360mm	OF	OFILE	OKY	OFILE	20




Warm-Up and Cool-Down Routine

The *warm-up* routine is an important part of any workout. The purpose of warming up is to prepare your body for exercise and to minimize injuries. Warm up for two to five minutes before aerobic exercising. It should begin every session to prepare your body for more strenuous exercise by heating up and stretching your muscles, increasing your circulation and pulse rate, and delivering more oxygen to your muscles.

Always perform a *cool-down* routine after your workout, repeat these exercises to reduce soreness in tired muscles. The purpose of cooling down is to return the body to its resting state at the end of each exercise session. A proper cool-down slowly lowers your heart rate and allows blood to return to the heart.

- **A. Head Roll** Rotate your head to the right for one second, you should feel a stretching sensation up the left side of your neck. Then rotate your head back for one second, stretching your chin to the ceiling and letting your mouth open. Rotate your head to the left for one second, then drop your head to your chest for one second.
- B. Shoulder Lift Lift your right shoulder toward your ear for one second. Then lift your left shoulder up for one second as you lower your right shoulder.
- **C. Side Stretch** Open your arms to the side and lift them until they are over your head. Reach your right arm as far toward the ceiling as you can for one second. Repeat this action with your left arm.
- **D. Quadricep Stretch** With one hand against a wall for balance, reach behind you and pull your right foot up. Bring your heel as close to your buttocks as possible. Hold for 15 seconds and repeat with left foot.
- E. Inner Thigh Stretch Sit with the soles of your feet together and your knees pointing outward. Pull your feet as close to your groin as possible, then gently push your knees toward the floor. Hold for 15 seconds.
- **F. Toe Touch** Slowly bend forward from your waist, letting your back and shoulders relax as you stretch toward your toes. Reach as far as you can and hold for 15 seconds.
- **G. Hamstring Stretch** Extend your right leg. Rest the sole of your left foot against your right inner thigh. Stretch toward your toe as far as possible. Hold for 15 seconds. Relax and then repeat with left leg.
- H. Calf/Achilles Stretch Lean against a wall with your right leg in front of the left and your arms forward. Keep your left leg straight and the right foot on the floor; then bend the right leg and lean forward by moving your hips toward the wall. Hold, then repeat on the other side for 15 seconds.







Some experts believe that the incorrect or prolonged use of almost any product may cause serious injury or death. To help reduce your risk of serious injury or death, refer to the information below. For more information, see www.datastreamserver.com/safety

- Consult all documentation, packaging and product labelling before use. Note that some products feature documentation available online. It is recommended to print and retain the documentation.
- Before each use, check the product for loose/broken/damaged/missing parts, wear or leaks (if applicable). Never use a product with loose/broken/damaged/missing parts, wear or leaks.
- Products must be inspected and serviced (if applicable) by a qualified technician every 6 months. This is based on average residential use by persons of average size and strength, and on a property of average metropolitan size. Use beyond these recommendations may require more frequent inspections/servicing.
- Ensure that all users of the product have completed a suitable industry recognised training course before being allowed access to the product.

- The product has been supplied by a general merchandise retailer that may not be familiar with your specific application or description of application. Be sure to attain third-party approval from a qualified specialist for your application before use, regardless of any assurances from the retailer or its representatives.
- This product is not intended for use where fail-safe operation is required. As with any product (for example, automobile, computer, toaster), there is the possibility of technical issues that may require the repair or replacement of parts, or the product itself. If the possibility of such failure and the associated time it may take to rectify could in any way inconvenience the user, business or employee, or financially affect the user, business or employee, then the product is not suitable for your requirements. This product is not intended for use where incorrect operation or a failure of any kind, including but not limited to, a condition requiring product return, replacement, parts replacement or service by a technician may cause financial loss, loss of employee time or an inconvenience requiring compensation.
- If this product has been purchased in error when considering the information presented here, contact the retailer directly for details of their returns policy, if required.



©2017 Proflex. All rights reserved. No part of this document, including descriptive content, concepts, ideas, diagrams or images may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying, scanning or recording, or any information storage and retrieval system, without express permission or consent from the publisher.